





## FEATURES /////

- ◆ Patented TensionMAX™ Design
- → Tension Eliminates Slack and Drift
- + Tension Tripod at Any Angle
- # Bubble Level
- ♣ Aircraft Grade Aluminum Tubes and Castings
- ♣ 3 ½"-8 Universal Mount Ring (Stainless Steel)
- # Bottom Hook For Adding Weight
- Adjustable Heights and Angles



Protected by US Patents:

US 10,738,938 B2 US 10,514,278 B1

TS\_rev10252021

HDP-PROTRIPOD

Americas, Asia-Pacific sales@metrologyworks.com Phone: 816-650-2266

Europe sales.eu@metrologyworks.com Phone: +49 162/1826504

## SPECIFICATIONS /////



Working Height: 29"-45", Weight: 48lbs

Lower Leg Stabilizer Knob



US 10,738,938 B2 US 10,514,278 B1



(Added Rigidity, Light Weight, Vibration Dampening)

Tension Hard Stop

QuickSlide™ Tension Nut + (Place the Tripod in Tension for Maximum Rigidity)

Ø44" Footprint with Legs Retracted Ø63" Footprint with Legs Extended

Tri-Foot • (Provides Stability on Rough and Uneven Surfaces)

Round Foot Kit Available

HDP-PROTRIPOD

MetrologyWorks, Inc. 105 S.E. Magellan Dr. Blue Springs, MO 64014 MetrologyWorks GmbH AM Stichkanal 14167 Berlin, Germany

